

Main cable junction terminal



HA 25-42

Main cable junction terminal

Productnumber: 69142201 Dimensions: 130 x 50 x 58 mm

Main cable junction terminal with cross-sectional area 1x25 $\rm mm^2$ per pole and 2 outlets 16 $\rm mm^2per$ pole

4-pole - 25/16 mm²

Technical Data

electrical characteristics

Rated operating voltage AC:	400 V
Number of poles:	4
Connection 1: Connection type:	Screws
Connection 1: Clamping points per pole:	3
Connection 1: Suitable for Cu conductors:	1
Connection 1: Connectable conductor cross-section, fine-wire with ferrule (min):	2.5 mm ²
Connection 1: Connectable conductor cross-section, fine-wire with ferrule (max):	16 mm²
Connection 1: Connectable conductor cross-section, single-wire (min):	1.5 mm²
Connection 1: Connectable conductor cross-section, single-wire (max):	25 mm²
Connection 1: Connectable conductor cross-section, stranded (min):	1.5 mm²
Connection 1:Connectable conductor cross- section, stranded (max):	25 mm²
Connection 2: Connection type:	Screws
Connection 2: Suitable for Cu conductors:	1
Connection 2: Connectable conductor cross-section, fine-wire with ferrule (min):	1.5 mm²
Connection 2: Connectable conductor cross-section, fine-wire with ferrule (max):	10 mm²
cross-section, mic-wire with remain (max):	
Connection 2: Connectable conductor cross-section, single-wire (min):	1.5 mm²
Connection 2: Connectable conductor	1.5 mm² 16 mm²
Connection 2: Connectable conductor cross-section, single-wire (min): Connection 2: Connectable conductor	

Dimensions

Width:	130 mm
Length:	50 mm
Height:	58 mm

Material characteristics

Flammability class according with UL94:	V0
Glow-wire flammability according to EN 60695-2-11:	960 °C
Industry quality:	no

mechanical properties

Connection 1: Tightening moment:	2.5 Nm
Connection 2: Tightening torque:	2.5 Nm

Material

Insulating body material:

Thermoplastic

Created at 29.04.2024. All statements without guarantee. We reserve the right to make improvements to technical progress. Günther Spelsberg GmbH + Co. KG

Im Gewerbepark 1 · D-58579 Schalksmühle · Telefon: +49 (0) 23 55 / 892-0 · Telefax: +49 (0) 23 55 / 892-299